

- UV stabilised external shell and shell material variants: steel, composite or aluminium
- 360 degree low energy LED lighting
- Fully segregated lighting compartment
- Height and width variants
- Designed for ease of installation and maintenance












## **SPECIFICATIONS**

Materials	Head: ABS Granulate Natural Polyethylene Body Internal: Hot-Dipped Galvanised Steel Body External: Powder Coated Aluminium / Aluminium Composite / 304 Stainless Steel BS EN-10204:2004, BS EN 573-3:2013, BS EN 755-2:2016
Dimensions	<b>A:</b> 750mm, 1000mm <b>B:</b> 885mm, 1135mm <b>C:</b> 205mm <b>D:</b> 185mm <b>E:</b> 135mm
Operating Temperature	-30°C to +60°C (Installed and Operated Within Multiple Climates from Around the Globe)
IP Rating	IP65
Compliances	BS7671 Wiring Regulations BS EN 61439-2:2011, BS EN 61439-5:2015 CE Certified Low Voltage Directive 2014/35/EU Electromagnetic Directive 2014/30/EU Powder Coated Corrosion Resistant / Salt Mist Tested Panels ISO 9227 UV Stabilised Flame Retardant to UL94
Typical Weight (AVG)	12-15kg (Standard 750mm)

Туре	G9 LED
Rating	5000k, 2x 2.3Watt, 240v, 50/60Hz
Protection	МСВ

## **OPTIONS**

- Shell colours and materials
- Branding vinyls
- Switching and control
- LED Colours









• Photocell controlled lighting



