

ROLECEV Sinexcel



ULTRACHARGE 160

Intelligent ultra-rapid EV charging station



ULTRACHARGE 160

Intelligent ultra-rapid EV charging station

Introducing our latest DC ultra-rapid charging station, UltraCharge 160.
This intelligent modular and scalable charger has the ability to be upgraded in modules of 20kW, all the way up to 160kW, making it the perfect futureproof and cost-effective solution for public, fleet and highway infrastructure deployment.

This high powered, advanced and robust charger is available in four standard power configurations; choose from 60kW, 80kW, 120kW or 160kW.

Offering convenient charging times for every EV with the ability to charge two vehicles simultaneously. Charging can be activated via either plug & charge, mobile app, RFID or contactless payment.

Designed with installers and chargepoint owner / operators in mind, these chargers are easy to install, maintain and service.







Product features

- Plug & charge, app, RFID or contactless payment controlled charging
- Offer up to 2x DC charging outputs
- Up to 160kW charging speeds (CHAdeMO up to 62.5kW | CCS2 up to 160kW)
- Upgradeable power modules
- OCPP 1.6 compliant (can integrate with any back-office)
- Over-the-air firmware / software updates
- Intelligent dynamic power sharing
- Supports static load management
- 7" HD user interface touch screen
- Integrated RFID / NFC / contactless card payment terminal
- 4G / Ethernet connectivity
- 96% Peak efficiency
- Ultrawide constant power output voltage range 300V 1000V
- Under/overvoltage, DC overcurrent, over-temp & surge protection
- 5m charging cables (4.5m external)
- Emergency stop
- IP55, IK10 protection rating
- Stocked in the UK by Rolec EV



Powered by

mobile app partners:

💢 Fuuse

wattif





OCPP 1.6 compliant

Ability to integrate with any OCPP compliant back-office management system and app.



Easy to operate

Four quick and easy ways to operate: contactless, mobile app, RFID cards and fobs or plug & charge.



Reliable & scalable EV charging solution

Offers world-class quality and reliability through field-proven infrastructure solutions.



4G and Ethernet enabled

Complete with secure 4G and Ethernet connectivity, ensuring chargers are always online 24/7.



Branding & colour options available

Rolec offers a bespoke chargepoint branding service; from logos & brand colours, to vinyl wraps.





DC Rapid charging connectors

Up to 160kW CCS charging connector(s) and/or up to 62.5kW CHAdeMO charging connector.



The details

UP TO 160KW

A variety of power configurations from 60kW to 160kW, flexible power distribution and dual connector models which can automatically switch the power according to the vehicle.

Choose from CCS2-dual and CCS2+CHAdeMO-dual outlets.

MAXIMISE YOUR

300V-1000V continuous power dual output segment, improves the power utilisation ratio of the DC charger, speeding up charging times and maximising revenue.

Delivers up to 80% charge in under 20 minutes.



POWER SHARING

The ULTRACHARGE 160 boasts the most advanced functionality for intelligent dynamic power sharing. Ideal for sites which require two vehicles to charge simultaneously.

SECURE

Packed with protection features including; under/overvoltage, DC overcurrent, over-temperature & surge protection.

Over-the-air updates allow the chargers to receive the very latest features, ensuring a safe and future-proof product 24/7.

WIDE OUTPUT RANGE

Ultra wide output voltage range 200V-1000V.

Not only can it meet the low-voltage charging needs of conventional EVs, but also meet the requirements for charging larger commercial vehicles such as HGVs and buses.



Specifications


Product Overview:

Station Level	Connection Type	Power Allocation	Input Current	Input Power	Unit Colour	Product Code
60kW DC	1x CCS2 1x CHAdeMO	1x 60kW**	112A	67kVA	○ White	EVDC2010
	2x CCS2	1x 60kW 1x 40kW / 1x20kW*	112A	67kVA	○ White	EVDC2015
80kW DC	2x CCS2	1x 80kW 2x 40kW*	150A	89kVA	○ White	EVDC2020
120kW DC	2x CCS2	1x 120kW 2x 60kW*	224A	133kVA	O White	EVDC2030
160kW DC	2x CCS2	1x 160kW 2x 80kW*	299A	177kVA	O White	EVDC2040


*When 2 vehicles are charging simultaneously


**Dual charging not supported

Flexible configuration



Model	Power Allocation		
120kW model configured to 100kW	1x 100kW 2x 50kW*		
	*When 2 vehicles are charging simultaneously		







Specifications

Technical Data:			
User Interface	 7 inch HD high-contrast touchscreen display Contactless card payment terminal RFID reader (ISO 14443 A + B to part 4 and ISO/IEC 15693, Mifare 1) NFC Plug & charge (ISO 15118) RGB LED status indicator Supported Languages - English (supports customising of other languages, available on request) 		
Charge Protocol	Mode 4 (IEC 61851-1)		
Protection	 Undervoltage & overvoltage protection DC overcurrent protection Over temperature protection Surge protection device Emergency stop button Optional tilt, flood and smoke detection Advanced dynamic power balancing Supports static load management (software configurable) 		
Input	 AC Input Voltage - 400V ± 10 % Input Frequency - 50 / 60 Hz Input Type - 3P + N + PE Power Factor - 0.99 THDi - <5% Grounding type - TT, TN-S, TN-CS 		
Output	 Connector Options - CCS2 and CHAdeMO (see page 5 for connector configurations) DC Output Voltage Range - CCS2: 200 to 1000 VDC, CHAdeMO: 200 to 500 VDC (300 to 1000 VDC is the output voltage of constant power output) Maximum Output Current - CCS: 200A, CHAdeMO: 125A Rated Power - DC: Up to 160kW (model dependent) Peak Efficiency - 96% Cable Length - 5m (4.5m exposed from the charger) 		
Communications	4GRJ45 Ethernet connectionOCPP 1.6J		
Dimensions	1000mm x 2000mm x 700mm (W x H x D)		
Weight	< 513kg (model dependant)		
Environmental	 Ingress Protection - IP55 Enclosure Protection - IK10 Operational Altitude - <2000 m Operating Temperature25 °C to +45 °C (full power) Temperature Derating - Up to 45 °C: 100% output power, 45-65 °C interval, linear power limit, 65 °C or more, module shutdown protection Storage Temperature Range30 °C to +70 °C Humidity - 5%-95% relative humidity, non-condensing Cooling Method - Air cooled 		
Materials	Body – 304 stainless steel Finish – all-weather powder-coated finish		
Unit Colour	White Other colours and branding options are available upon request		
Certifications & Compliances	 EV Charging Compliance - EN 61851, IEC 62196, DIN 70121, ISO 15118 Plug & Charge EMC Compliance - Class A (industrial) Certifications - CE, UKCA, TUV, TR25, RCM 		
Warranty	2 years (extended warranty available upon request)		



Chargepoint management



Monta's chargepoint management platform provides businesses and organisations with the ability to deploy and self-manage their very own electric vehicle charging network. Ideal for workplace, fleet, commercial and residential locations.



Of Unlock additional revenue streams

Set chargepoints for public and/or private use

Set different pricing for individual chargepoints & groups

Mr Dynamic pricing allows operators to set pricing in line with their hour-by-hour energy cost

+1 - Fully scalable solution; add or remove chargepoints & users

Complete fleet management solutions with analytical feedback & reporting

Reduce charging costs and CO_2 with Smart Charge feature

Vehicle integration provides visibility of battery size, SOC, percentage & location etc.


Automatically reimburse employees' home charging


Smart queuing system that sends notifications to drivers when they become available

Over-the-air updates and self-healing algorithms ensure charger stability & availability

5 Static, Dynamic or True Dynamic load balancing options

EV Roaming feature, allowing chargepoints to be available on other apps







For more information about Monta's chargepoint management solutions and pricing, see the Powered by Monta Overview Sheet



Chargepoint operation



Charge your EV on your terms. With Monta you have full control over your charging experience, at home or on the road.

- Easily locate and navigate using the chargepoint map
- Remotely control your home EV charging
- Choose your ready time and choose to prioritise lower costs, lower CO₂ or only using renewable energy
- Schedule charges so your car is ready when you are
- Integrate with most EV manufacturer apps and cars
- Real-time information on your car and battery levels to maximize your charging experience
- Share and give charging access to friends, family and guests
- Set your home charger for public use with custom pricing
- 🔼 Access to over 550,000 public chargepoints across Europe
- Easily initiate charging and complete payments via credit card, Apple Pay, Google Pay or Monta Wallet
- 24/7 online chat or email support for help when you need it most







RFID activation

Great for quick activation, RFID cards or key fobs are easily accessible and add for a much simpler charging experience, which can also be used alongside the mobile app.



DOWNLOAD THE APP





For more details about the Monta solution for EV drivers and the Monta app, please visit www.monta.com/uk/home-charging



THIS DOCUMENT CONTAINS INFORMATION THAT IS SUBJECT TO CHANGE WITHOUT NOTICE.

 $The \ latest\ version\ of\ this\ publication\ can \ be\ downloaded\ at\ https://www.rolecserv.com/downloads-ev-charging$

Illustrations of the product and user interface are for marketing purposes only.

Brand names, logos and trademarks used herein remain the property of their respective owners. This listing of any firm or their logos is not intended to imply any endorsement or direct affiliation with Rolec Services Ltd. and is purely to demonstrate branding opportunities.

© 2024 by Rolec Services Ltd. All rights reserved. EVUCD-V01-R4 UltraCharge 160 Data Sheet





t: 01205 724754

e: enquiries@rolecserv.co.uk

